




Pmax?	U	Ruhe	Max
	Udiff	250	215
	Ueff	35	
	Zo	24.75248	
		22000	
	Pmax(W)	0.027849	
	Pmax(mW)	27.84932	

Tube filament PT 220V-6V3 / 11K@8R - 2 systems in //

Zo OT	22k	k
-------	-----	---

BIAS at

V_g =	-0.9 V
I_a =	2 mA
I_s =	0 mA

Power consumption / section

Plate	3.7 mA
Screen	0 mA

TOTAL	3.7 mA
Overdrive	1.3
	4.81 mA
Qty sectic	2
	9.62 mA

Zener I 0 mA

DC-Need 9.62 mA

Factor 1.414


TRAFO 14 mA

Ratings 12AX7

Max. Plate	1 W
Max. Screen	0 W
V_a	250 V
I_a Max	4.0 mA
I_a bias 90%	3.6 mA
I_a bias 80%	3.2 mA

V_s	200 V
I_s Max	0 mA

la (mA) TR024 - 12AT7 TT u-Tracer V3.11.2 Is (ma)



Pmax?	U	Ruhe	Max
	Udiff	250	160
	Ueff	90	
	Zo	63.64922	
		22000	
	Pmax(W)	0.184147	
	Pmax(mW)	184.1465	

Tube filament PT 220V-6V3 / 11K@8R - 2 systems in //

Zo OT	22k	k
-------	-----	---

BIAS at

Vg =	-2.6 V
Ia =	6.5 mA
Is =	0 mA

Power consumption / section

Plate	9.5 mA
Screen	0 mA

TOTAL	9.5 mA
Overdrive	1.3

	12.35 mA
Qty sectic	1
	12.35 mA


Zener I	0 mA
---------	------

DC-Need	12.35 mA
Factor	1.414

TRAFO	17 mA
-------	-------

Ratings	12AT7
Max. Plate	2.5 W
Max. Screen	0 W
Va	250 V
Ia Max	10.0 mA
Ia bias 90%	9.0 mA
Ia bias 80%	8.0 mA

Vs	200 V
Is Max	0 mA



Pmax?	U	Ruhe	Max
	Udiff	250	180
	Ueff	70	
	Ueff	49.50495	
	Zo	22000	
	Pmax(W)	0.111397	
	Pmax(mW)	111.3973	

Tube filament PT 220V-6V3 / 11K@8R - 2 systems in //

Zo OT	22k	k
-------	-----	---

BIAS at

Vg =	-3 V
Ia =	4 mA
Is =	0 mA

Power consumption / section

Plate	7 mA
Screen	0 mA

TOTAL	7 mA
Overdrive	1.3
	9.1 mA
Qty sectic	2
	18.2 mA

Zener I	0 mA
---------	------


DC-Need	18.2 mA
Factor	1.414

TRAFO	26 mA
-------	-------

Ratings	12AY7
Max. Plate	1.5 W
Max. Screen	0 W
Va	250 V
Ia Max	6.0 mA
Ia bias 90%	5.4 mA
Ia bias 80%	4.8 mA

Vs	200 V
Is Max	0 mA

I_a (mA) TR001 - 12AU7 EH u-Tracer V3.11.2 I_s (ma)



$P_{max}?$	U	250	Max	120
	Udiff	130		
	Ueff	91.93777		
	Zo	22000		
	$P_{max}(W)$	0.384207		
	$P_{max}(mW)$	384.2069		

Tube filament PT 220V-6V3 / 11K@8R - 2 systems in //

Zo OT	22k	k
-------	-----	---

BIAS at

$V_g =$	-10 V
$I_a =$	7.5 mA
$I_s =$	0 mA

Power consumption / section

Plate	13 mA
Screen	0 mA

TOTAL	13 mA
Overdrive	1.3

16.9 mA	
Qty sectic	2
	33.8 mA

Zener I	0 mA
---------	------

DC-Need	33.8 mA
Factor	1.414

TRAFO	48 mA
-------	-------

Ratings	12BH7
Max. Plate	2.75 W
Max. Screen	0 W
V_a	250 V
I_a Max	11.0 mA
I_a bias 90%	9.9 mA
I_a bias 80%	8.8 mA


V_s	200 V
I_s Max	0 mA

I_a (mA)

TR020 - 12BH7 EH

u-Tracer V3.11.2

I_s (ma)



$P_{max}?$	U	250	Max
	Udiff	155	
	Ueff	109.6181	
	Zo	22800	
	$P_{max}(W)$	0.527023	
	$P_{max}(mW)$	527.0232	

Tube filament PT 220V-6V3 / 11K@8R - 2 systems in //

Zo OT	22k	k
-------	-----	---

BIAS at

$V_g =$	-11 V
$I_a =$	9 mA
$I_s =$	0 mA

Power consumption / section

Plate	15 mA
Screen	0 mA

TOTAL	15 mA
Overdrive	1.3
	19.5 mA
Qty sectic	2
	39 mA

Zener I

	0 mA
--	------

DC-Need

Factor	1.414
--------	-------

TRAFO

	55 mA
--	-------

Ratings 12BH7

Max. Plate	3.5 W
Max. Screen	0 W
V_a	250 V
I_a Max	14.0 mA
I_a bias 90%	12.6 mA
I_a bias 80%	11.2 mA

V_s	200 V
I_s Max	0 mA